



SANICERAMIC GROUP

www.ittspain.com  
 ittspain@ittspain.com  
 Tel.: 0034 964 626 309  
 Fax.: 0034 964 657 426  
 Ctra. de Alcora, Km. 7,5  
 12130 San Juan de Moró  
 Castellón (Spain)

QUALITY CERTIFICATE / CERTIFICADO DE CALIDAD

SIZES AND SURFACE QUALITY CARACTERÍSTICAS TÉCNICAS DE LAS BALDOSAS

PHOTOGRAPHY FOTOGRAFIA:

Series Serie OXIDE  
 Finishing of the piece Acabado  
 Colour Color  
 Nominal Size Medida Nominal 60X120  
 Work Size Medida Fabricación 607X1207X10,5  
 Norme Norma EN 14.411 Bla  
 Name Denominación GLAZED PORCELAIN/PORCELANICO ESMALTAD



SIZES AND SURFACE QUALITY DIMENSIONES Y ASPECTO SUPERFICIAL

Required/ Requisito	Value/ Valor
---------------------	--------------

Length and width Longitud y anchura	UNE-EN-ISO 10.545	Parte 2	%	±0,6%	Passes Standard Test Cumple
Thickness Espesor	UNE-EN-ISO 10.545	Parte 2	%	±5%	Passes Standard Test Cumple
Rectitud de los lados Measurement of Side Straightness	UNE-EN-ISO 10.545	Parte 2	%	±0,5%	Passes Standard Test Cumple
Squareness Ortogonalidad	UNE-EN-ISO 10.545	Parte 2	%	±0,5%	Passes Standard Test Cumple
Surface flatness Planitud de la superficie	UNE-EN-ISO 10.545	Parte 2			
Central curvature Curvatura central			%	±0,5%	Passes Standard Test Cumple
Edge curvature Curvatura lateral			%	±0,5%	Passes Standard Test Cumple
Warpage Alabeo			%	±0,5%	Passes Standard Test Cumple
Surface Quality Aspecto superficial			%	<0,5%	Passes Standard Test Cumple

PHYSICAL PROPERTIES PROPIEDADES FISICAS

Water Absorption Absorción de agua	UNE-EN-ISO 10.545	Parte 3	%	<0,5%	<0,5%
Breaking strength (N) Fuerza de rotura (N)	UNE-EN-ISO 10.545	Parte 4	N	>1300	>1300
Bending Strengt (N/mm <sup>2</sup> ) Resistencia a la flexión (N/mm <sup>2</sup> )	UNE-EN-ISO 10.545	Parte 4	N/mm <sup>2</sup>	>35	>35
Impact resistance Resistencia al impacto	UNE-EN-ISO 10.545	Parte 5		-	-
Resistance to abrasion Resistencia a la abrasión					
Deep Abrasión (UGL: Unglazed) Abrasión profunda (UGL: No esmaltadas)	UNE-EN-ISO 10.545	Parte 6	mm <sup>3</sup>	< 175	Passes Standard Test Cumple
Surface abrasion (GL: Glazed) Abrasión superficial (GL: Esmaltadas)	UNE-EN-ISO 10.545	Parte 7	PEI / Nº rev	-	II
Coefficient of thermal linear expansion Coeficiente de dilatación térmica lineal	UNE-EN-ISO 10.545	Parte 8	° C <sup>-1</sup>	-	9.10 <sup>-6</sup>
Resistance to thermal shock Resistencia al choque termico	UNE-EN-ISO 10.545	Parte 9		According to use Según Uso	-
Expansión por humedad Determination of moisture expansion	UNE-EN-ISO 10.545	Parte 10	mm/m		
Crazing resistance (GL: Glazed) Resistencia al cuarteo (GL: Esmaltadas)	UNE-EN-ISO 10.545	Parte 11		According to use Según Uso	-
Frost Resistance Resistencia a la helada	UNE-EN-ISO 10.545	Parte 12		-	-
Small differences of colour (GL: Glazed) Pequeñas diferencias de color (GL:Esmaltadas)	UNE-EN-ISO 10.545	Parte 16		ΔEcmc < 0,75	-
Small differences of colour (GL: Glazed) Pequeñas diferencias de color (UGL:No Esmaltadas)	UNE-EN-ISO 10.545	Parte 16		ΔEcmc < 1,0	-
Slip Resistance Deslizamiento:					
Slipperiness (Tortus) Coeficiente de fricción (Tortus)	ISO/DIS 10545	Parte 17		-	
Tilting Pendulo	UNE-ENV 12.633			-	CLASE 1
Slipway (boots) Rampa botas	DIN 51.130			-	R9
Slipway (Barefeet) Rampa (pies descalzos)	DIN 51.097			-	
Scratch resistance(Mohs) Resistencia al rayado (Mohs)	UNE-67101:1985			-	4

CHEMICAL PROPERTIES PROPIEDADES QUIMICAS

Chemical resistance Resistencia a productos químicos:	UNE-EN-ISO 10.545	Parte 13			
Resistance to low concentrations of acids and alkalis Resistencia a ácidos y álcalis de baja concentración				-	GLB
Resistance to high concentrations of acids and alkalis Resistencia a ácidos y álcalis de alta concentración				-	GHB
Resistance to household chemicals ans swimming pool salt productos domésticos y sales para piscinas				B	
Resistance to staining Resistencia a las manchas	UNE-EN-ISO 10.545	Parte 14		3	5
Emission of lead and cadmium Emisión de plomo y cadmio	UNE-EN-ISO 10.545	Parte 15		-	-

SAFETY SEGURIDAD

Euroclass. Fire resistance Euroclase. Resistencia al fuego	Decision 96/603/CE Modified Decision 96/603/CE Modificada			A1	
--	---	--	--	----	--